

INDUSTRIAL COMPONENT DATA

**EC4P-222-MTXX1 106400 0004519745 EATON ELECTRIC
Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CAN**

Brand: EATON - MOELLER | Manufacturer Part Number: EC4P-222-MTXX1



Manufacturer	EATON - MOELLER
MPN / Reference	EC4P-222-MTXX1
Catalog number	0004519745
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-BD294DCD6C
Generated	2026-08-04

Product Overview

Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CAN

EC4P-222-MTXX1

Compact controller for small and medium-sized automation tasks, programming according to IEC 61131 (CoDeSys), the Ethernet interface and the serial interface (ec4p-222 types) are for the purpose of programming, the communication via UDP and Modbus as well as connection of OPC clients

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EC4P PLCs

Additional Product Information

Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CANCompact controller for small and medium-sized automation tasks, programming according to IEC 61131 (CoDeSys), the Ethernet interface and the serial interface (ec4p-222 types) are for the purpose of programming, the communication via UDP and Modbus as well as connection of OPC clientsDelivery program

Expandable: Inputs/outputs and bus systems

individual laser inscription possible with EC4-COMBINATION-*DescriptioneasyNet/CANopen® and Ethernet on

boardInputsDigital12of which can be used as analog4OutputsTransistor8Supply voltage24 V DCTechnical data

GeneralDimensions (W x H x D)107.5 x 90 x 72 without/79 with adapter for MCC (6 SU) mmWeight0.3 kgMountingTop-hat

rail IEC/EN 60715, 35 mm or screw fixing using 3 fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/4

(AWG 22 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 22 - 12) mm2Standard screwdriver0.8 x 3.5 mmMax. tightening

torque0.6 NmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat

as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationLCD display (clearly legible)0 - 55 °CStorage [?]-40 - +70 °CRelative humidity, non-condensing (IEC/EN 60068-2-30)5 - 95 %Air pressure (operation)1080 - 1080 hPaAmbient conditions, mechanicalProtection type (IEC/EN 60529, EN50178, VBG 4)IP20Vibrations (IEC/EN 60068-2-6)Constant amplitude 0.15 mm10 - 57 HzVibrations (IEC/EN 60068-2-6)Constant...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EC4P-222-MTXX1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.