

INDUSTRIAL COMPONENT DATA

SL7-100-L-RYG-24LED 171425 Y7-171425 EATON ELECTRIC

Complete device red-yellow-green LED 24 V including base..

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-100-L-RYG-24LED



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-100-L-RYG-24LED
Catalog number	Y7-171425
Category	Signal tower complete
Minimum order	1 Pcs
Document ID	EO-443962C206
Generated	2026-08-05

Product Overview

Complete device;red-yellow-green; LED;24 V;including base 100mm

SL7-100-L-RYG-24LED

Eaton Moeller® series SL7 Complete device;red-yellow-green; LED;24 V;including base 100mm

Complete device, red-yellow-green, LED, 24 V AC/DC, including base 100mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Signal tower Catalog Number 171425 Model Code SL7-100-L-RYG-24LED EAN 4015081677573 Product Length/Depth 73 mm Product Height 373 mm Product Width 73 mm Product Weight 0.504 kg

Certifications CSA-C22.2 No. 94-91

UL File No.: E29184

UL report applies to both US and Canada

IEC/EN 60529

UL

CE

CSA Class No.: NKCR7

CSA-C22.2 No. 14-10

UL 508

UL Category Control No.: NKCR

Certified by UL for use in Canada

IEC/EN 60947-5-1 Catalog Notes The value specified for the leakage current shall apply per module. Features & Functions

Color Green

Yellow

Red Fitted with: 100 mm tube

Foot Light modules LED Number of modules 3 General

Connection to SmartWire-DT No Current consumption 0.049 - 0.054 A, at 24 V AC/DC

The value specified for the current consumption at 24 V AC/DC applies to each module. Degree of protection IP66

NEMA 4X, 13 Lifespan, electrical 100,000 h Light type Continuous light Loudness 0 dB Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Complete device Voltage type AC/DC Climatic environmental conditions Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Cli...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-100-L-RYG-24LED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.