

INDUSTRIAL COMPONENT DATA

BF-U-5/120-A 240740 EATON ELECTRIC Complete flush-mounted flat distribution board, white, 24 SU per row, 5 r..

Brand: EATON - MOELLER | Manufacturer Part Number: BF-U-5/120-A



Manufacturer	EATON - MOELLER
MPN / Reference	BF-U-5/120-A
Catalog number	240740
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-10140DD474
Generated	2026-08-01

Product Overview

Complete flush-mounted flat distribution board, white, 24 SU per row, 5 rows, type A

Complete BF-U-./..-A flush-mounted distribution board, white RAL 9016, 24 space units per row, 5 rows, height 920mm, width 588 mm, depth 136 mm, including door, front plates, DIN-rail mounting frame and neutral/PE terminals. Enclosure: closed design, including back plate, back plate can be used as a fixing plane, 2 cable gland plate inserts for slim distribution boards with a width of 24 space units, top, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out , 127 mm depth, terminals pre-assembled on enclosure (no loss of space units), 4 side fixing brackets. Sheet steel door with cam lock included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) and sheet steel door with transparent panel (BFZ-OTT-./...) are available as an accessory. Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated with installation kit , a universal mounting plate can be installed using an installation kit for flush-mounted enclosures (BFZ-U-MPL..). electrical contact for m...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Complete flush-mounted flat distribution board, white, 24 SU per row, 5 rows, type A Complete BF-U-./..-A flush-mounted distribution board, white RAL 9016, 24 space units per row, 5 rows, height 920mm, width 588 mm, depth 136 mm, including

door, front plates, DIN-rail mounting frame and neutral/PE terminals. Enclosure: closed design, including back plate, back plate can be used as a fixing plane, 2 cable gland plate inserts for slim distribution boards with a width of 24 space units, top, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out, 127 mm depth, terminals pre-assembled on enclosure (no loss of space units), 4 side fixing brackets. Sheet steel door with cam lock included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) and sheet steel door with transparent panel (BFZ-OTT-./...) are available as an accessory.

Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated with installation kit, a universal mounting plate can be installed using an installation kit for flush-mounted enclosures (BFZ-U-MPL..). electrical contact for metal front plate achieved with special lock on enclosure [

Delivery program

Basic function Basic devic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BF-U-5/120-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.