

INDUSTRIAL COMPONENT DATA

BF-U-4/132-A 240745 EATON ELECTRIC Complete flush-mounted flat distribution board, white, 33 SU per row, 4 r..

Brand: EATON - MOELLER | Manufacturer Part Number: BF-U-4/132-A



Manufacturer	EATON - MOELLER
MPN / Reference	BF-U-4/132-A
Catalog number	240745
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-987E65FD59
Generated	2026-08-01

Product Overview

Complete flush-mounted flat distribution board, white, 33 SU per row, 4 rows, type A

Complete BF-U-./..-A flush-mounted distribution board, white RAL 9016, 33 space units per row, 4 rows, height 770mm, width 750 mm, depth 136 mm, including door, front plates, DIN-rail mounting frame and neutral/PE terminals. Enclosure: closed design, including back plate, back plate can be used as a fixing plane, 3 cable gland plate inserts for slim distribution boards with a width of 33 space units, top, knockout cable entry openings on the bottom, terminals pre-assembled on enclosure (no loss of space units). Wall trough with door frame, back plate can be used as a fixing plane, cable entry openings that are easy to knock out , 127 mm depth, terminals pre-assembled on enclosure (no loss of space units), 4 side fixing brackets. Sheet steel door with cam lock included as standard, sheet steel door with expanded depth (required, for example, in order to install RMQ components in the door) (BFZ-OTR-./...) and sheet steel door with transparent panel (BFZ-OTT-./...) are available as an accessory. Removable DIN-rail mounting frame, for 45 mm modular installation devices, 150 mm DIN busbar distance, Eaton circuit-breakers can be integrated with installation kit , a universal mounting plate can be installed using an installation kit for flush-mounted enclosures (BFZ-U-MPL..). electrical contact for m...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xComfort BF small distribution board Catalog Number 240745 Model Code BF-U-4/132-A EAN

4015082407452 Product Length/Depth 140 mm Product Height 780 mm Product Width 760 mm Product Weight 16.4 kg
Compliances RoHS conform Certifications IEC/EN 61439-3
IEC/EN 62208
IEC/EN 61439-1 Delivery program
Type Basic device BF flat DBO Installation distribution boards Application Indoor (installation site) Color White
Traffic white (RAL 9016) Technical data - electrical
Voltage rating at AC 415 V AC Frequency rating of contacts 50 Hz / 60 Hz Technical data - mechanical
Closure type Other Enclosure material Steel Width in number of modular spacings 33 Mounting method DIN-rail
Flush mounted (plaster)
Flush mounting
Hollow wall
Hollow-wall mounting and flush mounting Material Sheet steel, powder-coated Degree of protection IP30
IK07 (impact resistance) Number of module space units per row 33 Number of rows 4 Terminal type Screw terminals PE
and N terminal number and cross section N: 2 x 25 mm² + 9 x 16 mm²
PE: 2 x 25 mm² + 58 x 16 mm² Built-in depth 140 mm Built-in height 780 mm Built-in width 760 mm Internal depth 127 mm
Cable entry position Cable entries on top and bottom Cover/door color White Cover/door model Closed Cover/door type
Door
Single Module rack type Rail frame Protective shrouding material Metal Temperature-rise verification as per IEC 60890
Heat diss. ambient 35°C delta T: 20°C flush mount individ. encl. top (IEC 60890) 60 W Heat diss. am...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BF-U-4/132-A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.