

**INDUSTRIAL COMPONENT DATA**

# BP-U-600/10-C 293316 2456191 EATON ELECTRIC Complete flush-mounting service distribution board with three-po..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-U-600/10-C



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | BP-U-600/10-C            |
| Catalog number  | 2456191                  |
| Category        | Small distribution board |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-77465B240E            |
| Generated       | 2026-08-05               |

## Product Overview

Complete flush-mounting service distribution board with three-point turn-lock, W600mm H1000mm  
 Flush-mounted service distribution board -?fully assembled, IP30, gray, RAL 7035, width 600 mm, outside height 1000 mm, 144 HP, 6 rows, incl. wall trough, top/bottom panels for the wall trough, flush-mounted door frame and assembly side panel, for MSW assembly configuration only, 240 mm mounting depth, incl. DIN-rail kit, includes front plates (150 mm) with device cutout (45 mm), earthed metal covers, ample wiring area, variable interior fittings with removable mounting frame, well-structured, multilayered design for easily accessible installation: assembly side panel - DIN-rails ... - enclosure, door can be right-hand or left-hand door

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

## Additional Product Information

Complete flush-mounting service distribution board with three-point turn-lock, W600mm H1000mm EL-Nummer (Norway) 2456191 Flush-mounted service distribution board -?fully assembled, IP30, gray, RAL 7035, width 600 mm, outside height 1000 mm, 144 HP, 6 rows, incl. wall trough, top/bottom panels for the wall trough, flush-mounted door frame and assembly side panel, for MSW assembly configuration only, 240 mm mounting depth, incl. DIN-rail kit, includes front plates (150 mm) with device cutout (45 mm), earthed metal covers, ample wiring area, variable interior fittings with removable mounting frame, well-structured, multilayered design for easily accessible installation: assembly side panel - DIN-rails ... - enclosure, door can be right-hand or left-hand door [ Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure, flush mounting [PV] 68 W Heat dissipation, at an ambient

temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, flush mounting [PV] 136 W IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-U-600/10-C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.