

INDUSTRIAL COMPONENT DATA

AKU35/10 107192 Y7-107192 EATON ELECTRIC Conductor connection terminal 4-35mm², 10 mm

Brand: EATON - MOELLER | Manufacturer Part Number: AKU35/10



Manufacturer	EATON - MOELLER
MPN / Reference	AKU35/10
Catalog number	Y7-107192
Category	Busbar terminal
Minimum order	50 Pcs
Document ID	EO-76F90F7E47
Generated	2026-08-05

Product Overview

Conductor connection terminal 4-35mm², 10 mm

AKU35/10

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Conductor connection terminal 4-35mm², 10 mm Universal conductor connection terminal, 4-35mm² AWG 10-AWG 2., directly terminated, 3x9x0.8 or 6x9x0.8, 270A, can be used for all 10mm thick flat busbars, width=15.5mm, termination space WxH=10.5x11mm, with integrated retaining spring, with open terminal chamber and captive fixing screw, can be used for SASY60i, SASY185i

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i busbar terminal Catalog Number 107192 Model Code AKU35/10 EAN 4015081069552 Product Length/Depth 16 mm Product Height 35 mm Product Width 29 mm Product Weight 0.047 kg
Compliances UL CSA09 (refer to approbation report)
RoHS conform Certifications UL (File No. E307559)
CE marking
CSA (File No. 236217)
North America (UL listed, CSA certified)
UL (Category Control Number NMTR2, NMTR8)
CSA-C22.2 No. 14

CSA (Class No. 3211-37)

IEC 60439-1

UL508A Delivery program

Type Technical data - electrical

Voltage rating (UL CSA 13) Max. 600 V AC Rated operation current (Ie) 270 A Rated operational current 270 A Rated operational current (Ie) - max 270 A Technical data - mechanical

Degree of protection UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking

Feeder circuits Busbar thickness - min 10 mm Busbar thickness - max 10 mm Busbar width - min 0 mm Busbar width - max 0 mm Terminal contact area 1.5 mm x 11 mm Terminal capacity (conductor) 4 mm² - 35 mm²

AWG 10 - AWG 2

9 mm x 0.8 mm (6x)

9 mm x 0.8 mm (3x) Conductor cross section - max 35 mm² Width clamp 15.5 mm Additional information

Functions Connections

Universal conductor connection terminal

Current limiting circuit breaker, refer to approbation report Special features With integrated retaining spring, open terminal chamber and captive terminal screw Suitable for Round conductor connection

Sector conductor connection

Strip conductor connection

Flat rail Used with Feeder circuits

All...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AKU35/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.