

INDUSTRIAL COMPONENT DATA

MFD-800-CAB5 266041 EATON ELECTRIC Connecting cable for MFD-CP8/10 to easy800, 5m, can be cut to desired len..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-800-CAB5



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-800-CAB5
Catalog number	266041
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-1CC878A8AD
Generated	2026-08-05

Product Overview

Connecting cable for MFD-CP8/10 to easy800, 5m, can be cut to desired length

Connection cable between MFD-CP8/CP10 to EASY800; 5 m

Connection cable, 5-Pole, can be used for easy800/MFD-CP8/CP10, for connection of the devices with each other via the serial interface, 5m, can be cut to desired length on one side, including plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

Connecting cable for MFD-CP8/10 to easy800, 5m, can be cut to desired length Connection cable, 5-Pole, can be used for easy800/MFD-CP8/CP10, for connection of the devices with each other via the serial interface, 5m, can be cut to desired length on one side, including plug Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan For use with easy800

MFD-...-CP8/CP10 Information relevant for export to North America Product Standards IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking

UL File No. E135462

UL Category Control No. NRAQ

CSA File No. 012528

CSA Class No. 2252-01 + 2258-02

North America Certification UL listed, CSA certified

Degree of Protection IEC: IP20, UL/CSA Type: -

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-800-CAB5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.