

**INDUSTRIAL COMPONENT DATA**

# EASY-NT-30 256283 0004520996 EATON ELECTRIC

## Connecting cable for networking devices via easyNet, 2xRJ45, 30cm

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-NT-30



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | EATON - MOELLER              |
| MPN / Reference | EASY-NT-30                   |
| Catalog number  | 0004520996                   |
| Category        | Data and communication cable |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-B18D9FF63F                |
| Generated       | 2026-08-05                   |

### Product Overview

Connecting cable for networking devices via easyNet, 2xRJ45, 30cm

EASY-NT-30

Connecting cable in the easyNet interconnection, prefabricated to 30 cm 2 RJ45 plugs at the ends

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > EASY programmable relays and MFD displays |
|--------------|-------------------------------------------------------------|

### Additional Product Information

EL-Nummer (Norway)4520996Connecting cable for networking devices via easyNet, 2xRJ45, 30cmConnecting cable in the easyNet interconnection, prefabricated to 30 cm 2 RJ45 plugs at the endsDelivery program

DescriptionConnection cable for XC200 to interface switchLength0.3 mFor use witheasy800

MFD-...-CP8...For use witheasyNetTechnical data

Pairs 2 x 0.14 mm<sup>2</sup>Conductor materialE-Cu 58 F21 nach DIN 40500 Teil 4Conductor materialMax. 0.49 mm (Cu wire bare 7 x 0.16 mm<sup>2</sup>)Core0.60 mm ±0.10 (dielectric polyethylene, halogen free, every two cores paired and twisted: wsbl-bl, wsor-or, wsgn-gn, wsbr-br)StrandingFour pairsSheath4.5 mm ± 0.2 (halogen free casing material, flame retardant (FRNC)) mm<sup>2</sup>Design verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdis]0 WOperating ambient temperature min.-25 °COperating

ambient temperature max. +55 °C IEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-NT-30 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.