

INDUSTRIAL COMPONENT DATA

CSAS3F3CY2205 136266 Y7-136266 EATON ELECTRIC

Connection cable, 3p, AC, coupling M12 flat, open end, L 5m

Brand: EATON - MOELLER | Manufacturer Part Number: CSAS3F3CY2205



Manufacturer	EATON - MOELLER
MPN / Reference	CSAS3F3CY2205
Catalog number	Y7-136266
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5AB1750F47
Generated	2026-08-05

Product Overview

Connection cable, 3p, AC, coupling M12 flat, open end, L=5m

CSAS3F3CY2205

Eaton Moeller® series CSAS Connection cable, 3p, AC, coupling M12 flat, open end, L=5m

Connecting cable, Basic function: Accessories, Length: 5000 mm, Voltage type: AC, 3 pole, Style output side: Cable end, open, Style input side: Coupling, straight, For use with: AC sensors, 3 pole, M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSAS Accessory Connection cable Catalog Number 136266 Model Code CSAS3F3CY2205 EAN 4015081330591 Product Length/Depth 203.2 mm Product Height 38.1 mm Product Width 177.8 mm Product Weight 0.41 kg Certifications CE Product specifications

Type Connecting cables Number Of Poles Three-pole Cable type Multi-core

Coupling, straight, Input side

Cable end, open, Output side Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category

Accessories Voltage type AC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C

Continuity resistor 0 m? Nominal current 0 A Cable length 5 m Cable sheath material Other Degree of protection Other

Color cable sheath Yellow Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact

body material Other Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature

of outer cable (assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max 70 °C Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (box-sided) Male (plug) Plug-in contact type (field-sided) Female (bus) Positioning cable feed (box-sided) Other Positioning cable feed (field-sided) Straight

ETIM for 136266 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

3

Type of electrical connection, field-s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSAS3F3CY2205 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.