

INDUSTRIAL COMPONENT DATA

CSDR4A3CY2205 136273 Y7-136273 EATON ELECTRIC

Connection cable, 4p/3Ltg, DC current, coupling m12 angled, op..

Brand: EATON - MOELLER | Manufacturer Part Number: CSDR4A3CY2205



Manufacturer	EATON - MOELLER
MPN / Reference	CSDR4A3CY2205
Catalog number	Y7-136273
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-198DA17EA0
Generated	2026-08-03

Product Overview

Connection cable, 4p/3Ltg, DC current, coupling m12 angled, open end, L=5m

CSDR4A3CY2205

Eaton Moeller® series CSDR Connection cable, 4p/3Ltg, DC current, coupling m12 angled, open end, L=5m

CSDR4A3CY2205

Connecting cable, Basic function: Accessories, Length: 5000 mm, Voltage type: DC, 4-pole, 3-conductor, Style output side:

Cable end, open, Style input side: Coupling, angled, For use with: DC sensors, 4 pole, 2 or 3-, wire connection, M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSDR Accessory Connection cable Catalog Number 136273 Model Code

CSDR4A3CY2205 EAN 4015081330652 Product Length/Depth 165.1 mm Product Height 25.4 mm Product Width 165.1 mm Product Weight 0.32 kg Certifications CE Product specifications

Type Connecting cables Number Of Poles Four-pole Cable type Coupling, angled, Input side

Cable end, open, Output side

Multi-core Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category Accessories Voltage type DC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Continuity resistor 0 m?

Nominal current 0 A Cable length 5 m Cable sheath material Other Degree of protection Other Color cable sheath Yellow
Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact body material Other
Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature of outer cable
(assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max 70 °C
Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (box-sided) Male (plug) Plug-in
contact type (field-sided) Female (bus) Positioning cable feed (box-sided) Other Positioning cable feed (field-sided) Angled
ETIM for 136273 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSDR4A3CY2205 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.