

INDUSTRIAL COMPONENT DATA

CSDR4A4CY2202 136279 Y7-136279 EATON ELECTRIC

Connection cable, 4p, DC current, coupling m12 angled, open en..

Brand: EATON - MOELLER | Manufacturer Part Number: CSDR4A4CY2202



Manufacturer	EATON - MOELLER
MPN / Reference	CSDR4A4CY2202
Catalog number	Y7-136279
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E36E0204F3
Generated	2026-08-04

Product Overview

Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m

CSDR4A4CY2202

Eaton Moeller® series CSDR Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m

Connecting cable, Basic function: Accessories, Range: connecting cables, Length: 2000 mm, Voltage type: DC, 4 pole, Style output side: Cable end, open, Style input side: Coupling, angled, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12, RS2...-02..., RS2...-11..., RS4-02...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSDR Accessory Connection cable Catalog Number 136279 Model Code CSDR4A4CY2202 EAN 4015081330706 Product Length/Depth 152.4 mm Product Height 44.45 mm Product Width 152.4 mm Product Weight 0.23 kg Certifications CE Product specifications

Type Connecting cables Number Of Poles Four-pole Cable type Cable end, open, Output side

Multi-core

Coupling, angled, Input side Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category Accessories Voltage type DC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C

Continuity resistor 0 m? Nominal current 0 A Cable length 2 m Cable sheath material Other Degree of protection Other
Color cable sheath Yellow Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact
body material Other Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature
of outer cable (assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max
70 °C Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (box-sided) Male (plug)
Plug-in contact type (field-sided) Female (bus) Positioning cable feed (box-sided) Other Positioning cable feed (field-sided)
Angled

ETIM for 136279 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSDR4A4CY2202 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.