

INDUSTRIAL COMPONENT DATA

+NZM2-4-XKRO 266766 Y7-266766 EATON ELECTRIC

Connection, on rear, top 4p. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM2-4-XKRO



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM2-4-XKRO
Catalog number	Y7-266766
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-81F4C08396
Generated	2026-08-03

Product Overview

Connection, on rear, top 4p. Can only be sold assembled.

+NZM2-4-XKRO

Connection, on rear, top 4p

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. O = for fitting at the top. U = for fitting at the bottom. Can be used for: NZM2(-4), PN2(-4), N2(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Connection, on rear, top 4pOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. O = for fitting at the top. U = for fitting at the bottom. Can be used for: NZM2(-4), PN2(-4), N2(-4)

General specificationsProduct nameEaton Moeller series NZM connection typePart no.+NZM2-4-XKROEAN4015082667665Product Length/Depth140 millimetreProduct height35 millimetreProduct width60 millimetreProduct weight0.422 kilogramCompliancesIEC
RoHS conformProduct TradenameNZMProduct TypeAccessoriesProduct Sub TypeConnection typeDelivery programTypeAccessoryConnection on rearTerminalNumber of polesFour-poleAmperage Rating300 A (Cu), 250 A

(Al)FrameNZM2Suitable forAluminum cable lug

Copper cable lugs

Four-poleUsed withNZM2-4, PN2-4, N2-4Technical Data - MechanicalMounting positionFitted aboveTechnical Data -

Mechanical - TerminalsTerminal capacity (stranded cable)4 mm² - 70 mm² (2x)

10 mm² - 50 mm² (2x)

10 mm² - 185 mm² (1x)

10 mm² - 50 mm² (1x)Terminal capacity (copper busbar)Max. 24 mm x 8 mm

Min. 16 mm x 5 mmTerminal capacity (copper strip)2 segments of 16 mm x 0.8 mm - 6 segments of 24 mm x 0.5 mmDesign
verification as per IEC/EN 6143910.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verif...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM2-4-XKRO with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.