

INDUSTRIAL COMPONENT DATA

BPZ-CB-44/14 102722 Y7-102722 EATON ELECTRIC

Connection segment for 1-pole terminal block, L x W x H 16 x 44..

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-CB-44/14



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-CB-44/14
Catalog number	Y7-102722
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-D20E3DDF8E
Generated	2026-08-05

Product Overview

Connection segment for 1-pole terminal block, L x W x H = 16 x 44 x 14 mm

BPZ-CB-44/14

Eaton xEnergy Basic LV systems Low voltage switchgear. Connection segment for 1-pole terminal block, L x W x H = 16 x 44 x 14 mm

27-mm connection segment for 1-pole terminal block, BPZ-CB suitable for BPZ-KB-6/125, dimensions (LxWxH) 16 x 44 x 14 mm, equipment supplied: 1 connection segment

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 102722 Model Code BPZ-CB-44/14 EAN 4015081025824 Product Length/Depth 44 mm Product Height 16 mm Product Width 14 mm Product Weight 0.03 kg
Compliances RoHS conform Delivery program

Color Other Number of phases 1 Number of poles Single-pole Technical data - electrical

Rated operational voltage (Ue) - max 690 V Rated surge voltage 1 KV Rated uninterrupted current (Iu) 125 A Rated conditional short-circuit current (Iq) 0 kA Rated short-time withstand current (Icw) 4.2 kA Electric connection type Fork
Technical data - mechanical

Number of modular spacings 0 Cross section 20 mm² Pitch dimensions 0 mm Suitable for number of devices 2 Additional information

Features Insulated Suitable for 2 devices

ETIM for 102722 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1

Number of poles (EF001391)

1

Suitable for number of devices (EF007241)

2

Module width (EF007504)

0 mm

Cross section (EF000649)

20 mm²

Length (EF001438)

44 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

0

Rated permanent current I_u (EF001389)

125 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

1 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rated operation voltage U_e (EF007357)

690 V

Rated short-time withstand current I_{cw} (EF007050)

4.2 kA

Suitable for devices with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-CB-44/14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.