

INDUSTRIAL COMPONENT DATA

K95/3 025017 Y7-25017 EATON ELECTRIC Connection terminal, 160A, 3p, flat/round

Brand: EATON - MOELLER | Manufacturer Part Number: K95/3



Manufacturer	EATON - MOELLER
MPN / Reference	K95/3
Catalog number	Y7-25017
Category	Rail terminal bar
Minimum order	1 Pcs
Document ID	EO-765236B2EA
Generated	2026-08-02

Product Overview

Connection terminal, 160A, 3p, flat/round

Terminal connection, 160A, 3P, flat/round

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 160A, 3p, flat/round K connecting terminals, for AL and CU, one side round and the other side flat, rated operational current $I_e=160$ A, number pole=3, terminal capacities: Copper round cable stranded, sectoral stranded, round cable solid, sectoral solid and aluminium round conductor solid, sectoral solid=1x16-95mm² or aluminum sectoral solid=1x35-70mm². Other side: copper band 3x9x0.8 up to 6x9x0.8 or Cu bar=18x4mm, notes: Conversion kits for strip terminal in cable connection available separately, terminal covers available separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure Catalog Number 025017 Model Code K95/3 EAN 4015080250173 Product Length/Depth 100 mm Product Height 115 mm Product Width 99 mm Product Weight 1.436 kg Compliances RoHS conform Product specifications

Special features Type Accessory panel building

General switchboard accessory

Features Contact safe Accessory/spare part type Terminals, 160 - 1000 A

Terminations Used with General switchboard accessory

Accessory panel building Connection type Clamp

Screwing Number of poles Three-pole Rated operation current (Ie) 160 A Mounting method Screw Suitable for Useful for stranded conductors Terminal capacity (copper band) 9 mm x 0.8 mm (3x) - 9 mm x 0.8 mm (6x) for flat strip Nominal current 160 A Number of connections (Less Than 6 mm squared) 0 Number of connections (Less Than AWG 6) 0 Number of connections (Greater Than 25 mm squared) 6 Number of connections (Greater Than 250 kcmil) 0 Number of connections (10 mm squared) 0 Number of connections (16 mm squared) 0 Number of connections (25 mm squared) 0 Number of connections (250 kcmil) 0 Number of connections (AWG 2) 0 Number of connections (AWG 4) 0 Number of connections (AWG 4/0) 0 Number of connections (AWG 6) 0 Number of connections (total) 6 Rated insulation voltage (Ui) 1000 VAC Number of outputs 1 Terminal capacity (aluminum cable) 35 mm² - 70 mm² (1x) Terminal capacity (conductor) 18 mm x 4 mm Terminal capacity (copper/a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K95/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.