

INDUSTRIAL COMPONENT DATA

K150/4 034509 Y7-34509 EATON ELECTRIC Connection terminal, 250A, 4p, flat/round

Brand: EATON - MOELLER | Manufacturer Part Number: K150/4



Manufacturer	EATON - MOELLER
MPN / Reference	K150/4
Catalog number	Y7-34509
Category	Rail terminal bar
Minimum order	1 Pcs
Document ID	EO-1CE3F8CDB3
Generated	2026-08-04

Product Overview

Connection terminal, 250A, 4p, flat/round

Terminal connection, 250A, 4p, flat/round

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 250A, 4p, flat/round K connecting terminals, for AL and CU, one side round and the other side flat, rated operational current $I_e=250$ A, poles=4, terminal capacities: Copper round cable stranded, sectoral stranded, round cable solid, sectoral solid and aluminium round conductor solid, sectoral solid=1x35-150 mm² or 2x16-70 or aluminum sectoral solid=1x50-120 or 2x35-50. Other side: copper band 1x(4x16x0.8) to 2x(6x16x0.8) or Cu bar=18x4 mm, notes: Conversion kits for strip terminal in cable connection available separately, terminal covers available separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure Catalog Number 034509 Model Code K150/4 EAN 4015080345091 Product Length/Depth 100 mm Product Height 115 mm Product Width 130 mm Product Weight 2.35 kg Compliances RoHS conform Delivery programme

Type Accessory/spare part type Terminals, 160 - 1000 A

Terminations Nominal current 250 A Number of poles Four-pole Technical data - electrical

Rated insulation voltage (Ui) 1000 VAC Rated operation current (Ie) 250 A Technical data - mechanical

Mounting method Screw Number of connections (10 mm squared) 0 Number of connections (16 mm squared) 0 Number of

connections (25 mm squared) 0 Number of connections (250 kcmil) 0 Number of connections (Less Than 6 mm squared) 0
Number of connections (Less Than AWG 6) 0 Number of connections (Greater Than 25 mm squared) 8 Number of
connections (Greater Than 250 kcmil) 0 Number of connections (AWG 2) 0 Number of connections (AWG 4) 0 Number of
connections (AWG 4/0) 0 Number of connections (AWG 6) 0 Number of connections (total) 8 Number of inputs 1 Number of
outputs 2 Terminal capacity (aluminum cable) 35 mm² - 50 mm² (2x)
50 mm² - 120 mm² (1x) Terminal capacity (conductor) 18 mm x 4 mm Terminal capacity (copper band) 1 segment of 16 mm
x 0.8 mm (4x) - 2 segments of 16 mm x 0.8 mm (6x) for flat strip Terminal capacity (copper/aluminum cable) 35 mm² - 150
mm² (1x)
16 mm² - 70 mm² (2x) Conductor cross section, input - min 16 mm² Conductor....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K150/4 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.