


INDUSTRIAL COMPONENT DATA

K2X240/4 048747 Y7-48747 EATON ELECTRIC Connection terminal, 630A, 4p, flat/round

Brand: EATON - MOELLER | Manufacturer Part Number: K2X240/4



Manufacturer	EATON - MOELLER
MPN / Reference	K2X240/4
Catalog number	Y7-48747
Category	Rail terminal bar
Minimum order	1 Pcs
Document ID	EO-83DD6D283E
Generated	2026-08-03

Product Overview

Connection terminal, 630A, 4p, flat/round

Terminal Connection, 630A, 4P, Flat/Round

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 630A, 4p, flat/round K connecting terminals, for AL and CU, one side round and the other side flat, rated operational current $I_e=630$ A, number pole=4, terminal capacities: Copper round cable stranded, sectoral stranded, round cable solid, sectoral solid and aluminium round conductor solid, sectoral solid=1x150-300 or 2x50-240mm² or aluminum, sectoral solid=1x150-240 or 2x95-185mm². Other side: copper band 10x16x0.8 up to 11x21x1 or Cu bar=40x15mm, notes: Conversion kits for strip terminal in cable connection available separately, terminal covers available separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure Catalog Number 048747 Model Code K2X240/4 EAN 4015080487470 Product Length/Depth 225 mm Product Height 140 mm Product Width 254 mm

Product Weight 6.94 kg Compliances RoHS conform Delivery programme

Type Accessory/spare part type Terminals, 160 - 1000 A

Terminations Nominal current 630 A Number of poles Four-pole Technical data - electrical

Rated insulation voltage (Ui) 1000 VAC Rated operation current (Ie) 630 A Technical data - mechanical

Mounting method Screw Number of connections (10 mm squared) 0 Number of connections (16 mm squared) 0 Number of

connections (25 mm squared) 0 Number of connections (250 kcmil) 0 Number of connections (Less Than 6 mm squared) 0
Number of connections (Less Than AWG 6) 0 Number of connections (Greater Than 25 mm squared) 8 Number of
connections (Greater Than 250 kcmil) 0 Number of connections (AWG 2) 0 Number of connections (AWG 4) 0 Number of
connections (AWG 4/0) 0 Number of connections (AWG 6) 0 Number of connections (total) 8 Number of inputs 1 Number of
outputs 2 Terminal capacity (aluminum cable) 150 mm² - 240 mm² (1x)
95 mm² - 185 mm² (2x) Terminal capacity (conductor) 40 mm x 15 mm Terminal capacity (copper band) 21 mm x 1 mm
(11x) for flat strip
16 mm x 0.8 mm (10x) for flat strip Terminal capacity (copper/aluminum cable) 150 mm² - 300 mm² (1x)
50 mm² - 240 mm² (2x) Conductor cross section, input - min 70 mm² Conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K2X240/4 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.