

INDUSTRIAL COMPONENT DATA

M22-KC01 216382 Y7-216382 EATON ELECTRIC Contact element, 1 N/C, base fixing, 6. contact, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: M22-KC01



Manufacturer	EATON - MOELLER
MPN / Reference	M22-KC01
Catalog number	Y7-216382
Category	Auxiliary contact block
Minimum order	1 unit
Document ID	EO-30C78A7642
Generated	2026-08-05

Product Overview

Contact element, 1 N/C, base fixing, 6. contact, screw connection

M22-KC01

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A
M22-KC01

Contact element, Connection technique: Screw terminals, Fixing: Base fixing, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.8, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Degree of Protection: IP20, Connection to SmartWire-DT: no, Connection type: Single contact, Standards: IEC 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of contacts as change-over contact (EF008257)	0
Number of contacts as normally open contact (EF008256)	0
Number of contacts as normally closed contact (EF008255)	1
Number of fault-signal switches (EF007613)	0
Rated operation current I _e at AC-15, 230 V (EF001385)	6 A
Type of electric connection (EF003961)	Screw connection
Model (EF000010)	Clip-on
Mounting method (EF000003)	Floor fastening
Lamp holder (EF000048)	None

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Contact element Catalog Number 216382 Model Code M22-KC01
EAN 4015082163822 Product Length/Depth 38 mm Product Height 10 mm Product Width 32 mm Product Weight 0.01 kg

Compliances CE Marked Certifications IEC 60947-5

CSA Std. C22.2 No. 14-05

EN 60947-5

CSA Std. C22.2 No. 94-91

UL 508

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

CE

CSA File No.: 012528

IEC/EN 60947-5

UL

UL File No.: E29184

UL Category Control No.: NKCR

CSA

IEC 60947-5-1 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Electric connection type Screw connection General

Degree of protection IP20 Lifespan, electrical 700,000 Operations (at 230 V, AC-15, 3 A)

1,600,000 Operations (at 230 V, 0.5 A)

1,000,000 Operations (at 230 V, AC-15, 1 A)

1,200,000 Operations (at 12 V, DC-13, 2.8 A) Lifespan, mechanical 5,000,000 Operations Model Top mounting Mounting method Floor fastening Operating frequency 3600 Operations/h Operating torque 0.8 Nm Overvoltage category III Pollution degree....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-KC01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.