

INDUSTRIAL COMPONENT DATA

M22-KC10 216380 Y7-216380 EATON ELECTRIC Contact element, 1N/O, base fixing, 6. contact, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: M22-KC10



Manufacturer	EATON - MOELLER
MPN / Reference	M22-KC10
Catalog number	Y7-216380
Category	Auxiliary contact block
Minimum order	1 unit
Document ID	EO-76B527ED5C
Generated	2026-08-06

Product Overview

Contact element, 1N/O, base fixing, 6. contact, screw connection

M22-KC10

Eaton Moeller® series M22 Contact element, Make contact, Bottom, Screw terminals, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

Contact element, Connection technique: Screw terminals, Fixing: Base fixing, Contacts N/O = Normally open: 1 N/O, Degree of Protection: IP20, Connection to SmartWire-DT: no, Connection type: Single contact, Standards: IEC 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of contacts as change-over contact (EF008257)	0
Number of contacts as normally open contact (EF008256)	1
Number of contacts as normally closed contact (EF008255)	0
Number of fault-signal switches (EF007613)	0
Rated operation current Ie at AC-15, 230 V (EF001385)	6 A
Type of electric connection (EF003961)	Screw connection
Model (EF000010)	Clip-on
Mounting method (EF000003)	Floor fastening
Lamp holder (EF000048)	None

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Contact element

Catalog Number 216380

Model Code M22-KC10

EAN 4015082163808

Product Length/Depth 38 mm

Product Height 10 mm

Product Width 32 mm

Product Weight 0.01 kg

Compliances CE Marked

Certifications EN 60947-5

UL 508

CSA Std. C22.2 No. 14-05

IEC 60947-5

CSA Std. C22.2 No. 94-91

VDE

IEC/EN 60947-5

UL Category Control No.: NKCR

CSA

UL

CSA Class No.: 3211-03

CSA File No.: 012528

UL File No.: E29184

CSA-C22.2 No. 14-05

CE

CSA-C22.2 No. 94-91

IEC 60947-5-1

Features & Functions

Color Green

Electric connection type Screw connection

General information

Degree of protection IP20

Lifespan, electrical 1,200,000 Operations (at 12 V, DC-13, 2.8 A)

1,000,000 Operations (at 230 V, AC-15, 1 A)

1,600,000 Operations (at 230 V, 0.5 A)

700,000 Operations (at 230 V, AC-15, 3 A)

Lifespan, mechanical 5,000,000 Operations

Model Top mounting

Mounting method Floor fastening

Operating frequency 3600 Operations/h

Operating torque 0.8 Nm

Overvoltage category III

Pollution degree 3

Rated impulse withstand voltage (Uimp) 6000 V AC
Ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-KC10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.