

INDUSTRIAL COMPONENT DATA

M22-CK10 216384 Y7-216384 EATON ELECTRIC Contact element, 1N/O, front mount, 6. contact, spring clamp connec..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-CK10



Manufacturer	EATON - MOELLER
MPN / Reference	M22-CK10
Catalog number	Y7-216384
Category	Auxiliary contact block
Minimum order	20 Pcs
Document ID	EO-9E123B1313
Generated	2026-08-05

Product Overview

Contact element, 1N/O, front mount, 6. contact, spring clamp connection

M22-CK10

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A
Contact element, Standard/Approval: UL/CSA, IEC, Construction size: NZM1/2/3/4, Connection technique: Cage Clamp,
Fixing: Front fixing, Description: Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany,
Contacts N/O = Normally open: 1 N/O, Degree of Protection: IP20, Connection to SmartWire-DT: no, Connection type:
Single contact, Description of HIA trip-indicating auxiliary contact: General trip indication '+', when tripped by shunt release,
overload release, short-circuit release or by the residual-current release due to residual-current., Can be used with NZM1, 2
, 3 circuit-breaker: a trip-indicating auxiliary contact can be clipped into the circuit-breaker., Can be used with NZM4
circuit-breaker: up to two standard auxiliary contacts can be clipped into t

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Contact element Catalog Number 216384 Model Code M22-CK10
EAN 4015082163846 Product Length/Depth 38 mm Product Height 10 mm Product Width 32 mm Product Weight 0.01 kg
Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

EN 60947-5

IEC 60947-5

CE

CSA File No.: 012528

CSA-C22.2 No. 94-91

IEC 60947-5-1

UL

UL Category Control No.: NKCR

CSA Class No.: 3211-03

UL/CSA

UL File No.: E29184

CSA

IEC

IEC/EN 60947-5

CSA-C22.2 No. 14-05 Features & Functions

Color Green Electric connection type Spring clamp connection General

Degree of protection IP20 Lifespan, electrical 1,600,000 Operations (at 230 V, 0.5 A)

700,000 Operations (at 230 V, AC-15, 3 A)

1,200,000 Operations (at 12 V, DC-13, 2.8 A)

1,000,000 Operations (at 230 V, AC-15, 1 A) Lifespan, mechanical 5,000,000 Operations Model Top mounting and

integrable Mounting method Front fastening Operating frequency 3600 Operations/h Overvoltage category III Pollution

degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Type Auxiliary contact Used

with Can be used with NZM1 circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM2 size circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM4 circuit-breaker: up to two standard auxiliary contacts can be clipped into the circuit-breaker.

Can be use...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-CK10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.