

INDUSTRIAL COMPONENT DATA

M22-CK20 107898 Y7-107898 EATON ELECTRIC Contact element, 2N/O, front mount, spring clamp connection

Brand: EATON - MOELLER | Manufacturer Part Number: M22-CK20



Manufacturer	EATON - MOELLER
MPN / Reference	M22-CK20
Catalog number	Y7-107898
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-77B7CD5D47
Generated	2026-08-02

Product Overview

Contact element, 2N/O, front mount, spring clamp connection

M22-CK20

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 2 N/O, 24 V 3 A, 220 V 230 V 240 V 4 A
Contact element, Standard/Approval: UL/CSA, IEC, Construction size: NZM1/2/3/4, Connection technique: Cage Clamp,
Fixing: Front fixing, Description: When using emergency switching off actuators M22-PV... max. 2 contact elements = 4 NC
/ N/O contacts, Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany, Contacts N/O =
Normally open: 2 N/O, Degree of Protection: IP20, Connection to SmartWire-DT: no, Connection type: Double contact,
Description of HIA trip-indicating auxiliary contact: General trip indication '+', when tripped by shunt release, overload
release , short-circuit release or by the residual-current release due to residual-current., Can be used with NZM1, 2, 3
circuit-breaker: a trip-indicating auxiliary contact can be clipped into the circuit-breaker.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Contact element Catalog Number 107898 Model Code M22-CK20
EAN 4015081075355 Product Length/Depth 43 mm Product Height 10 mm Product Width 38 mm Product Weight 0.012 kg
Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05
EN 60947-5
CSA Std. C22.2 No. 94-91

UL 508

IEC 60947-5

CSA

CE

CSA Class No.: 3211-03

IEC/EN 60947-5

UL

CSA File No.: 012528

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

UL/CSA

IEC

IEC 60947-5-1

UL File No.: E29184

UL Category Control No.: NKCR Features & Functions

Electric connection type Spring clamp connection General

Degree of protection IP20 Model Top mounting and integrable Mounting method Front fastening Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Type Auxiliary contact Used with Can be used with NZM3, 4 circuit-breaker: up to three standard auxiliary contacts can be clipped into the circuit-breaker.

Can be used with NZM1 circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM1, 2, 3 circuit-breaker: a trip-indicating auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM2 size circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM4 circuit-breaker: up to two standard auxiliary contacts can be clipped into the circuit-breaker.

Climatic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-CK20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.