

INDUSTRIAL COMPONENT DATA

M22-SWD-K11 115964 Y7-115964 EATON ELECTRIC Contact function element, SmartWire-DT, 1W, front mount

Brand: EATON - MOELLER | Manufacturer Part Number: M22-SWD-K11



Manufacturer	EATON - MOELLER
MPN / Reference	M22-SWD-K11
Catalog number	Y7-115964
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-98E16DDF83
Generated	2026-08-01

Product Overview

Contact function element, SmartWire-DT, 1W, front mount

M22-SWD-K11

Eaton Moeller® series M22 Function element, for combination with RMQ-Titan operating elements M22-..., 1 changeover contact, Front fixing

Function element, Fixing: Front fixing, Connection to SmartWire-DT: yes

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Function element Catalog Number 115964 Model Code M22-SWD-K11 EAN 4015081157044 Product Length/Depth 40 mm Product Height 42 mm Product Width 10 mm Product Weight 0.009 kg

Certifications CSA Class No.: 3211-07

IEC/EN 61131-2

EN 50178

UL

CSA File No.: 2324643

CSA

UL Category Control No.: NKCR

UL File No.: E29184

BV

LRS Features & Functions

Electric connection type Flat plug-in connection Functions For combination with RMQ-Titan operating elements M22-...

Diagnosis function General

Degree of protection IP20 Model Top mounting Mounting method Front fastening Overvoltage category Not applicable

Pollution degree 2 Product category SmartWire-DT RMQ connections Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Environmental conditions Condensation: prevent with appropriate measures Relative humidity 9 - 95 % (non-condensing, IEC/EN 60068-2-30) Ele...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-SWD-K11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.