

INDUSTRIAL COMPONENT DATA

DILM50(24V50HZ) 277817 Y7-277817 EATON ELECTRIC Contactor, 3p, 22kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM50(24V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM50(24V50HZ)
Catalog number	Y7-277817
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-7563E31B1F
Generated	2026-08-05

Product Overview

Contactor, 3p, 22kW/400V/AC3

DILM50(24V50HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 22 kW, 24 V 50 Hz, AC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277817 Model Code DILM50(24V50HZ) EAN 4015082778170 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 0.872 kg

Compliances CE Marked Certifications EN 60947-4-1

IEC 60947-4-1

CSA Std. C22.2 No. 14-05

UL 508

VDE

IEC/EN 60947

UL

UL 60947-4-1

UL Category Control No.: NLDX

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CE

VDE 0660

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

UL File No.: E29096

CSA Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS3 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 m Ω Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type AC Ambient conditions, mechanical Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM50(24V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.