

INDUSTRIAL COMPONENT DATA

DILM50(240V50HZ) 277819 Y7-277819 EATON ELECTRIC Contactor, 3p, 22kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM50(240V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM50(240V50HZ)
Catalog number	Y7-277819
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-8CBC91C04D
Generated	2026-08-06

Product Overview

Contactor, 3p, 22kW/400V/AC3

DILM50(240V50HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 22 kW, 240 V 50 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: $I_e = 50$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 80$ A, enclosed: $I_{th} = 58$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 162$ A, enclosed: $I_{th} = 145$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 15.5$ kW, 380 V 400 V: $P = 22$ kW, 660 V 690 V: $P = 30$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 6$ kW, 380 V 400 V: $P = 10$ kW, 660 V 690 V: $P = 14$ kW, Can be combined with auxiliary contact: DILM150-XHI(V).., DILM1000-XHI(V).., Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277819 Model Code DILM50(240V50HZ) EAN

4015082778194 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 0.872 kg

Compliances CE Marked Certifications EN 60947-4-1

UL 508

CSA Std. C22.2 No. 14-05

IEC 60947-4-1

VDE

IEC/EN 60947-4-1

CSA File No.: 012528

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04

UL File No.: E29096

UL

UL Category Control No.: NLDX

CSA

CE

VDE 0660

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947 Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS3 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating

frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN

50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 m Ω Suitable for Also motors with

efficiency class IE3 Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical

Shock resistance 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Ha...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM50(240V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.