

INDUSTRIAL COMPONENT DATA

DILM50(600V60HZ) 277825 XTCE050D00D EATON ELECTRIC Contactor, 3p, 22kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM50(600V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM50(600V60HZ)
Catalog number	XTCE050D00D
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-859AB997DE
Generated	2026-08-05

Product Overview

Contactor, 3p, 22kW/400V/AC3

Power contactor; Screw connection; 3 poles; 50 A; 22 kW; 400 V;

Contactor, 3 pole, 380 V 400 V 22 kW, 600 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 50 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole , 50 - 60 Hz Open at 40 °C: I_{th} =I_e= 80 A, enclosed: I_{th}= 58 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 162 A, enclosed: I_{th}= 145 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 15.5 kW, 380 V 400 V: P= 22 kW, 660 V 690 V: P= 30 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 6 kW, 380 V 400 V: P= 10 kW, 660 V 690 V: P= 14 kW, Can be combined with auxiliary contact: DILM150-XHI(V).., DILM1000-XHI(V).., Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277825 Model Code DILM50(600V60HZ) EAN

4015082778255 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 0.872 kg

Certifications IEC/EN 60947

CSA

VDE 0660

UL Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS3 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating

frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN

50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 m Ω Suitable for Also motors with

efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type AC Ambient conditions, mechanical

Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM50(600V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.