

INDUSTRIAL COMPONENT DATA

DILM65(RDC240) 277911 Y7-277911 EATON ELECTRIC Contactor, 3p, 30kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM65(RDC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM65(RDC240)
Catalog number	Y7-277911
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-25A86B055D
Generated	2026-08-05

Product Overview

Contactor, 3p, 30kW/400V/AC3

DILM65(RDC240)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 30 kW, RDC 240: 200 - 240 V DC, DC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 65 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 98 A, enclosed: I_{th}= 72 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 200 A, enclosed: I_{th}= 180 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 20 kW, 380 V 400 V: P= 30 kW, 660 V 690 V: P= 35 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 7 kW, 380 V 400 V: P= 12 kW, 660 V 690 V: P= 17 kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, Volt...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277911 Model Code DILM65(RDC240) EAN 4015082779115 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 1.052 kg

Certifications CSA File No.: 012528

CE

CSA

CSA Class No.: 2411-03, 3211-04

IEC/EN 60947

UL File No.: E29096

VDE 0660

UL

IEC/EN 60947-4-1

UL 60947-4-1

UL Category Control No.: NLDX

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS3 Lifespan, mechanical 10,000,000 Operations (DC operated) Operating frequency 5000 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 mΩ Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type DC Ambient conditions, mechanical

Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM65(RDC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.