

## INDUSTRIAL COMPONENT DATA

# DILMC65(48V50HZ) 278015 XTCEC065D00Y EATON ELECTRIC Contactor, 3p, 30kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC65(48V50HZ)



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | DILMC65(48V50HZ)              |
| Catalog number  | XTCEC065D00Y                  |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-AC25D2FF3A                 |
| Generated       | 2026-08-04                    |

## Product Overview

Contactor, 3p, 30kW/400V/AC3

DILMC65(48V50HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 30 kW, 48 V 50 Hz, AC operation, Spring-loaded terminals Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Spring-cage terminals on auxiliary and control circuit terminals, Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V:  $I_e = 65$  A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C:  $I_{th} = I_e = 98$  A, enclosed:  $I_{th} = 72$  A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open:  $I_{th} = 200$  A, enclosed:  $I_{th} = 180$  A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 20 kW, 380 V 400 V: P= 30 kW, 660 V 690 V: P= 35 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 7 kW, 380 V 400 V: P= 12 kW, 660 V 690 V: P= 17 kW, Can be combined with auxiliary contact: DILM150-XHIC(V)..., DILM1000-XHIC..., Instructions: C...

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Contactors up to 170A

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 278015 Model Code DILMC65(48V50HZ) EAN

4015082780159 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 0.872 kg

Certifications CSA File No.: 012528

CSA

IEC/EN 60947-4-1

CSA Class No.: 2411-03, 3211-04

UL 508

CSA-C22.2 No. 14-05

VDE 0660

UL

CE

IEC/EN 60947

UL File No.: E29096

UL Category Control No.: NLDX Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS3 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 m $\Omega$ ? Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical Shock resistance 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 w...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC65(48V50HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.