

INDUSTRIAL COMPONENT DATA

DILM80(42V50/60HZ) 239407 Y7-239407 EATON ELECTRIC Contactor, 3p, 37kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM80(42V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM80(42V50/60HZ)
Catalog number	Y7-239407
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-1F2C956555
Generated	2026-08-05

Product Overview

Contactor, 3p, 37kW/400V/AC3

DILM80(42V50/60HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 37 kW, 42 V 50/60 Hz, AC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239407 Model Code DILM80(42V50/60HZ) EAN 4015082394073 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.18 kg

Certifications UL 60947-4-1

IEC/EN 60947

CSA File No.: 012528

CSA

CSA Class No.: 2411-03, 3211-04

UL File No.: E29096

IEC/EN 60947-4-1

UL Category Control No.: NLDX

VDE 0660

CSA-C22.2 No. 60947-4-1-14

CE

UL Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 7,000,000 Operations (Coil 50/60 Hz)

10,000,000 Operations (AC operated) Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage

category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 m Ω ? Suitable for Also motors with efficiency class IE3 Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical Shock resistance 5 g, N/C auxiliary contact, Mechanical, according to IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM80(42V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.