

INDUSTRIAL COMPONENT DATA

DILM95(RDC24) 239510 Y7-239510 EATON ELECTRIC Contactor, 3p, 45kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM95(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM95(RDC24)
Catalog number	Y7-239510
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-65FD9DBBFF
Generated	2026-08-03

Product Overview

Contactor, 3p, 45kW/400V/AC3

DILM95(RDC24)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 45 kW, RDC 24: 24 - 27 V DC, DC operation, Screw terminals DILM95(RDC24)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le}= 95 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_{le}= 130 A, enclosed: I_{th}= 100 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 275 A, enclosed: I_{th}= 250 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 30 kW, 380 V 400 V: P= 45 kW, 660 V 690 V: P= 75 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 16 kW, 380 V 400 V: P= 26 kW, 660 V 690 V: P= 35 kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating elec...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239510 Model Code DILM95(RDC24) EAN 4015082395100 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.32 kg
Certifications CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

IEC/EN 60947-4-1

VDE 0660

UL 60947-4-1

UL Category Control No.: NLDX

UL

CSA File No.: 012528

CSA

IEC/EN 60947

CE

CSA Class No.: 2411-03, 3211-04 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 10,000,000 Operations (DC operated) Operating frequency 3600 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 mΩ Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running
AC-1: Non-inductive or slightly inductive loads, resistance furnaces
AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type DC Ambient conditions, mechanical Shock resistance 5 g, N/C auxiliary contact, Mechanical, a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM95(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.