

INDUSTRIAL COMPONENT DATA

DILMC95(RDC24) 239715 Y7-239715 EATON ELECTRIC Contactor, 3p, 45kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC95(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMC95(RDC24)
Catalog number	Y7-239715
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-17149D9835
Generated	2026-08-05

Product Overview

Contactor, 3p, 45kW/400V/AC3

DILMC95(RDC24)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 45 kW, RDC 24: 24 - 27 V DC, DC operation, Spring-loaded terminals DILMC95(RDC24)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.,

Description: Spring-cage terminals on auxiliary and control circuit terminals, Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 95 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 130 A, enclosed: I_{th} = 100 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 275 A, enclosed: I_{th} = 250 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 30 kW, 380 V 400 V: P = 45 kW, 660 V 690 V: P = 75 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 16 kW, 380 V 400 V: P = 26 kW, 660 V 690 V: P = 35 kW, Can be combined with auxiliary contact:

DILM150-XHIC(V) .., DILM10...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239715 Model Code DILMC95(RDC24) EAN

4015082397159 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.25 kg

Certifications IEC/EN 60947-4-1

VDE 0660

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

UL

CE

CSA

IEC/EN 60947

UL Category Control No.: NLDX

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 10,000,000 Operations (DC operated) Operating

frequency 3600 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN

50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the

electronics with "0" signal) Resistance per pole 0.6 m Ω Suitable for Also motors with efficiency class IE3 Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type DC Ambient conditions, mechanical

Shock resistance 5 g, N/C auxiliary contact, Mechanical,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC95(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.