

INDUSTRIAL COMPONENT DATA

**DILM115(RAC240) 239548 Y7-239548 EATON ELECTRIC
101442 DILM32-XTEE11(RAC240)**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM115(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM115(RAC240)
Catalog number	Y7-239548
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-BEE438D23D
Generated	2026-08-06

Product Overview

101442 DILM32-XTEE11(RAC240)

DILM115(RAC240)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 55 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals DILM115(RAC240)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le} = 115 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_{le} = 160 A, enclosed: I_{th} = 115 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 325 A, enclosed: I_{th} = 285 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 37 kW, 380 V 400 V: P = 55 kW, 660 V 690 V: P = 90 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 17 kW, 380 V 400 V: P = 28 kW, 660 V 690 V: P = 43 kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., integrated suppressor circuit in....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor

Catalog Number 239548

Model Code DILM115(RAC240)

EAN 4015082395483

Product Length/Depth 160 mm

Product Height 170 mm

Product Width 90 mm

Product Weight 2.25 kg

Certifications CSA Class No.: 2411-03, 3211-04

CSA

CSA File No.: 012528

VDE 0660

UL

IEC/EN 60947-4-1

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

CE

IEC/EN 60947

UL Category Control No.: NLDX

Catalog Notes Contacts according to EN 50012

Features & Functions

Fitted with: Suppressor circuit in actuating electronics

Number of poles Three-pole

Number of poles Three-pole

Number of poles Three-pole

General information

Application Contactors for Motors

Connection Screw terminals

Frame size FS4

Lifespan, mechanical 10,000,000 Operations (AC operated)

Operating frequency 3600 mechanical Operations/h (AC operated)

Overvoltage category III

Pollution degree 3

Product category Contactors

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp) 8000 V AC

Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal)

Resistance per pole 0.6 mΩ

Suitable for Also motors with efficiency class IE3

Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Voltage ty...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM115(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.