

INDUSTRIAL COMPONENT DATA

DILM115(RAC440) 239549 Y7-239549 EATON ELECTRIC Contactor, 3p, 55kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM115(RAC440)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM115(RAC440)
Catalog number	Y7-239549
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-DBD8EF1CD8
Generated	2026-08-06

Product Overview

Contactor, 3p, 55kW/400V/AC3

DILM115(RAC440)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 55 kW, RAC 440: 380 - 440 V 50/60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 115 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole , 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 160 A, enclosed: I_{th}= 115 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 325 A, enclosed: I_{th}= 285 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 37 kW, 380 V 400 V: P= 55 kW, 660 V 690 V: P= 90 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 17 kW, 380 V 400 V: P= 28 kW, 660 V 690 V: P= 43 kW, Can be combined with auxiliary contact: DILM150-XHI(V).., DILM1000-XHI(V).., Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electr...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239549 Model Code DILM115(RAC440) EAN 4015082395490 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.25 kg
Compliances CE Marked Certifications IEC 60947-4-1

EN 60947-4-1

CSA Std. C22.2 No. 14-05

UL 508

VDE

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLDX

CSA Class No.: 2411-03, 3211-04

CE

VDE 0660

UL 60947-4-1

CSA

IEC/EN 60947-4-1

UL File No.: E29096

UL

CSA File No.: 012528 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 m Ω Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running
AC-4: Normal AC induction motors: starting, plugging, reversing, inching
AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type AC Am...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM115(RAC440) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.