

INDUSTRIAL COMPONENT DATA

**DILMC150(RAC240) 239751 Y7-239751 EATON ELECTRIC
101442 DILM32-XTEE11(RAC240)**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC150(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMC150(RAC240)
Catalog number	Y7-239751
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-D2E2ED3042
Generated	2026-08-04

Product Overview

101442 DILM32-XTEE11(RAC240)

DILMC150(RAC240)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 75 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Spring-loaded terminals DILMC150(RAC240)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Spring-cage terminals on auxiliary and control circuit terminals, Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: $I_e = 150$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 190$ A, enclosed: $I_{th} = 144$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 400$ A, enclosed: $I_{th} = 360$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 48$ kW, 380 V 400 V: $P = 75$ kW, 660 V 690 V: $P = 96$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 20$ kW, 380 V 400 V: $P = 33$ kW, 660 V 690 V: $P = 48$ kW, Can be combined with auxiliary contact: DILM150-XHI...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239751 Model Code DILMC150(RAC240) EAN

4015082397517 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.273 kg

Certifications IEC/EN 60947

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04

UL Category Control No.: NLDX

CSA File No.: 012528

IEC/EN 60947-4-1

UL

UL File No.: E29096

CE

CSA-C22.2 No. 60947-4-1-14

CSA

VDE 0660 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating

frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN

50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the

electronics with "0" signal) Resistance per pole 0.4 mΩ Suitable for Also motors with efficiency class IE3 Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Ambient conditions, mechanical

Shock resistance 7 g, N/O auxiliary contact, Mechanical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC150(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.