

INDUSTRIAL COMPONENT DATA

DILM32-01(208V60HZ) 277286 Y7-277286 EATON ELECTRIC Contactor, 3p+1N/C, 15kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-01(208V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-01(208V60HZ)
Catalog number	Y7-277286
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-71ABB8763C
Generated	2026-08-06

Product Overview

Contactor, 3p+1N/C, 15kW/400V/AC3

DILM32-01(208V60HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 15 kW, 1 NC, 208 V 60 Hz, AC operation, Screw terminals Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 32 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole , 50 - 60 Hz Open at 40 °C: I_{th} =I_e= 45 A, enclosed: I_{th}= 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 100 A, enclosed: I_{th}= 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 10 kW, 380 V 400 V: P= 15 kW, 660 V 690 V: P= 17 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 4 kW, 380 V 400 V: P= 7 kW, 660 V 690 V: P= 10 kW, Can be combined with auxiliary contact: DILA-XHI(V)..., Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., with mirror contact., Voltage AC/DC: AC op...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277286 Model Code DILM32-01(208V60HZ) EAN

4015082772864 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm Product Weight 0.428 kg

Certifications CE

IEC/EN 60947-4-1

CSA Class No.: 2411-03, 3211-04

VDE 0660

UL 508

UL File No.: E29096

CSA File No.: 012528

UL

CSA

IEC/EN 60947

UL Category Control No.: NLDX

CSA-C22.2 No. 14-05 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS2 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7 m Ω ? Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Ambient conditions, mechanical Shock resistance 6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, accordin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-01(208V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.