

INDUSTRIAL COMPONENT DATA

**DILM32-01(230V50HZ,240V60HZ) 277292 Y7-277292 EATON
ELECTRIC 277292 DILM32-01(230V50HZ,240V60HZ)**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-01(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-01(230V50HZ,240V60HZ)
Catalog number	Y7-277292
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-0E67DDD5C5
Generated	2026-08-06

Product Overview

277292 DILM32-01(230V50HZ,240V60HZ)

DILM32-01(230V50HZ,240V60HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 15 kW, 1 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals DILM32-01(230V50HZ,240V60HZ)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le}= 32 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_{le}= 45 A, enclosed: I_{th}= 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 100 A, enclosed: I_{th}= 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 10 kW, 380 V 400 V: P= 15 kW, 660 V 690 V: P= 17 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 4 kW, 380 V 400 V: P= 7 kW, 660 V 690 V: P= 10 kW, Can be combined with auxiliary contact: DILA-XHI(V)..., DILM32-XHI11-S, Contacts N/C = Normally closed: 1 NC, Instruction...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor

Catalog Number 277292

Model Code DILM32-01(230V50HZ,240V60HZ)

EAN 4015082772925

Product Length/Depth 97 mm

Product Height 85 mm

Product Width 45 mm

Product Weight 0.428 kg

Certifications CSA Certified

UL Listed

IEC 60947-4-1

EN 60947-4-1

VDE 0660

IEC/EN 60947

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

UL Category Control No.: NLDX

UL

UL 60947-4-1

CE

CSA

Catalog Notes Contacts according to EN 50012

Features & Functions

Fitted with: Mirror contact

Number of poles Three-pole

Number of poles Three-pole

Number of poles Three-pole

General information

Application Contactors for Motors

Connection Screw terminals

Frame size FS2

Lifespan, mechanical 10,000,000 Operations (AC operated)

Operating frequency 5000 mechanical Operations/h (AC operated)

Overvoltage category III

Pollution degree 3

Product category Contactors

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp) 8000 V AC

Resistance per pole 2.7 m Ω

Suitable for Also motors with efficiency class IE3

Type Full voltage reversing small contactor

Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Voltage type AC

A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-01(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.