

INDUSTRIAL COMPONENT DATA

**DILMC32-01(230V50/60HZ) 277739 XTCEC032C01G2 EATON
ELECTRIC Contactor, 3p+1N/C, 15kW/400V/AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC32-01(230V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMC32-01(230V50/60HZ)
Catalog number	XTCEC032C01G2
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-884E2CB5E3
Generated	2026-08-06

Product Overview

Contactor, 3p+1N/C, 15kW/400V/AC3

Power Contactor Push-in connection 3 poles + 1 NC 32 A 15 kW

Contactor, 3 pole, 380 V 400 V 15 kW, 1 NC, 230 V 50/60 Hz, AC operation, Spring-loaded terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.,

Description: Spring-cage terminals on auxiliary and control circuit terminals, Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le}= 32 A , Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 45 A, enclosed: I_{th} = 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 100 A, enclosed: I_{th} = 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 10 kW, 380 V 400 V: P= 15 kW, 660 V 690 V: P= 17 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 4 kW, 380 V 400 V: P= 7 kW, 660 V 690 V: P= 10 kW, Can be combined with auxiliary contact: DILA-XHIC(V)..., Conta...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277739 Model Code DILMC32-01(230V50/60HZ)
EAN 4015082777395 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm Product Weight 0.433 kg

Certifications CSA File No.: 012528

VDE 0660

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 2411-03, 3211-04

UL Category Control No.: NLDX

CSA

CE

IEC/EN 60947-4-1

UL 60947-4-1

UL File No.: E29096

UL Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS2 Lifespan, mechanical 10,000,000 Operations (AC operated)

7,000,000 Operations (Coil 50/60 Hz) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7 mΩ Suitable for Also motors with efficiency class IE3 Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical Shock resistance 3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoid...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC32-01(230V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.