

## INDUSTRIAL COMPONENT DATA

**DILMC9-01(\*V50HZ) 277497 EATON ELECTRIC DOL starter, 3p, 2.2-7.5kW/400V/AC3, 100kA, protection electronic**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC9-01(\*V50HZ)



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | DILMC9-01(*V50HZ)             |
| Catalog number  | -                             |
| Category        | Power contactor, AC switching |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-A07C17E9F5                 |
| Generated       | 2026-08-05                    |

**Product Overview**

DOL starter, 3p, 2.2-7.5kW/400V/AC3, 100kA, protection electronic

Power contactor; Pressure connection; 3 poles + 1 NC; 9 A; 4 kW; 400 V; AC-3; \* V 50 Hz

Contactor, 3 pole, 380 V 400 V 4 kW, 1 NC, \*V 50 Hz, AC operation, Spring-loaded terminals

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Contactors up to 170A

**Additional Product Information**

Contactor, 3 pole, 380 V 400 V 4 kW, 1 NC, \*V 50 Hz, AC operation, Spring-loaded terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I<sub>th</sub> = I<sub>e</sub> = 22 A, enclosed: I<sub>th</sub> = 18 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I<sub>th</sub> = I<sub>e</sub> = 22 A, enclosed: I<sub>th</sub> = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I<sub>th</sub> = 50 A, enclosed: I<sub>th</sub> = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.5 kW, 380 V 400 V: P = 4 kW, 660 V 690 V: P = 4.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1.5 kW, 380 V 400 V: P = 2.5 kW, 660 V 690 V: P = 3.6 kW, Can be combined with auxiliary contact: DILA-XHIC(V)..  
Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Auxiliary current, coil, and main current terminals with spring-cage connection technology., with mirror contact., Voltage AC/DC: AC operation

Delivery program

Product rangeContactorsApplicationContactors for....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC9-01(\*V50HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.