

## INDUSTRIAL COMPONENT DATA

# DILMC12-01(\*V60HZ) 277562 EATON ELECTRIC Contactor AC-3/400 V: 5, 5 kW 3 pole AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC12-01(\*V60HZ)



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | DILMC12-01(*V60HZ)            |
| Catalog number  | -                             |
| Category        | Power contactor, AC switching |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-B117FFC732                 |
| Generated       | 2026-08-05                    |

## Product Overview

Contactor AC-3/400 V: 5, 5 kW 3 pole AC

Power contactor; Snap-in connection; 3 poles + 1 NC; 12 A; 5.5 kW; 400 V; AC-3; \* V 60 Hz

Contactor, 3 pole, 380 V 400 V 5.5 kW, 1 NC, \*V 60 Hz, AC operation, Spring-loaded terminals

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | EATON - MOELLER > Contactors up to 170A |
|--------------|-----------------------------------------|

## Additional Product Information

Contactor, 3 pole, 380 V 400 V 5.5 kW, 1 NC, \*V 60 Hz, AC operation, Spring-loaded terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I<sub>le</sub> = 12 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I<sub>th</sub> = I<sub>le</sub> = 22 A, enclosed: I<sub>th</sub> = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I<sub>th</sub> = 50 A, enclosed: I<sub>th</sub> = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 3.5 kW, 380 V 400 V: P = 5.5 kW, 660 V 690 V: P = 6.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 2 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 4.4 kW, Can be combined with auxiliary contact: DILA-XHIC(V)..  
Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Auxiliary current, coil, and main current terminals with spring-cage connection technology., with mirror contact., Voltage AC/DC: AC operation

Delivery program

Product rangeContactorsApplicationContactors for...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC12-01(\*V60HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.