

INDUSTRIAL COMPONENT DATA

DILM17-01(48V50HZ) 277024 Y7-277024 EATON ELECTRIC Contactor, 3p+1N/C, 7.5kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM17-01(48V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM17-01(48V50HZ)
Catalog number	Y7-277024
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-7C145E2646
Generated	2026-08-05

Product Overview

Contactor, 3p+1N/C, 7.5kW/400V/AC3

DILM17-01(48V50HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, 48 V 50 Hz, AC operation, Screw terminals
DILM17-01(48V50HZ)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 18 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 40 A, enclosed: I_{th} = 32 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 88 A, enclosed: I_{th} = 80 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 5 kW, 380 V 400 V: P = 7.5 kW, 660 V 690 V: P = 11 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 2.5 kW, 380 V 400 V: P = 4.5 kW, 660 V 690 V: P = 6.5 kW, Can be combined with auxiliary contact: DILA-XHI(V) .., Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., with mirror contact...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277024 Model Code DILM17-01(48V50HZ) EAN 4015082770242 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm Product Weight 0.428 kg

Certifications CSA Class No.: 2411-03, 3211-04

VDE 0660

CSA File No.: 012528

IEC/EN 60947-4-1

UL

CSA-C22.2 No. 14-05

IEC/EN 60947

UL Category Control No.: NLDX

CE

UL 508

CSA

UL File No.: E29096 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS2 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 5000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 2.7 mΩ Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical

Shock resistance 6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5.3 g, N/O auxiliary contact, Mechanical, acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM17-01(48V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.