

INDUSTRIAL COMPONENT DATA

DILM15-01(*VDC) 290113 EATON ELECTRIC Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Brand: EATON - MOELLER | Manufacturer Part Number: DILM15-01(*VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM15-01(*VDC)
Catalog number	290113
Category	Power contactor, AC switching
Minimum order	10 Pcs
Document ID	EO-35A4367C7F
Generated	2026-08-04

Product Overview

Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Power contactor; Screw connection; 3 poles + 1 NC; 15 A; 7.5 kW;

Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, *V DC, DC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 15.5 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 22 A, enclosed: I_{th}= 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 50 A, enclosed: I_{th}= 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 4 kW, 380 V 400 V: P= 7.5 kW, 660 V 690 V: P= 7 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 2 kW, 380 V 400 V: P= 3 kW, 660 V 690 V: P= 4.4 kW, Can be combined with auxiliary contact: DILA-XHI(V)..
Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Integrated varistor suppressor circuit., with mirror contact., Voltage AC/D...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, *V DC, DC operation, Screw terminals
Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors:

starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: $I_e = 15.5$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 22$ A, enclosed: $I_{th} = 18$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 50$ A, enclosed: $I_{th} = 45$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 4$ kW, 380 V 400 V: $P = 7.5$ kW, 660 V 690 V: $P = 7$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 2$ kW, 380 V 400 V: $P = 3$ kW, 660 V 690 V: $P = 4.4$ kW, Can be combined with auxiliary contact: DILA-XHI(V)..., Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Integrated varistor suppressor circuit., with mirror contact., Voltage AC/DC: DC operation

General specifications Product name Eaton Moeller® series DILM Contactor Part no. DILM15-01(*VDC) Product Length/Depth 75 millimetre Product height 68 millimetre Product width 45 millimetre Product weight 0.296 kilog...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM15-01(*VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.