

INDUSTRIAL COMPONENT DATA

**DILMC15-01(220VDC) 293965 XTCEC015B01BD EATON
ELECTRIC Contactor, 3p+1N/C, 7.5kW/400V/AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMC15-01(220VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMC15-01(220VDC)
Catalog number	XTCEC015B01BD
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-DC8A56ACE4
Generated	2026-08-04

Product Overview

Contactor, 3p+1N/C, 7.5kW/400V/AC3

Power Contactor Push-in connection 3 poles + 1 NC 15 A 7.5 kW

Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, 220 V DC, DC operation, Spring-loaded terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le} = 15.5 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_{le} = 22 A, enclosed: I_{th} = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 50 A, enclosed: I_{th} = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 4 kW, 380 V 400 V: P = 7.5 kW, 660 V 690 V: P = 7 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 2 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 4.4 kW, Can be combined with auxiliary contact: DILA-XHIC(V)..
Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Auxiliary current, coil, and main current terminals with spring-cage connecti...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, 220 V DC, DC operation, Spring-loaded terminals
Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction

motors: starting, plugging, reversing, inching, Connection technique: Spring-loaded terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: $I_e = 15.5$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 22$ A, enclosed: $I_{th} = 18$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 50$ A, enclosed: $I_{th} = 45$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 4$ kW, 380 V 400 V: $P = 7.5$ kW, 660 V 690 V: $P = 7$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 2$ kW, 380 V 400 V: $P = 3$ kW, 660 V 690 V: $P = 4.4$ kW, Can be combined with auxiliary contact: DILA-XHIC(V)..., Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., Auxiliary current, coil, and main current terminals with spring-cage connection technology., Integrated varistor suppressor circuit., with mirror contact., Voltage AC/DC: DC operation Delivery program
Product range Contactors Application Contactors for Motors Subrange Contactors up...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMC15-01(220VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.