

## INDUSTRIAL COMPONENT DATA

**DILM7-10(\*V60HZ) 276563 EATON ELECTRIC Contactor, 3p + 1N / O, 3kW / 400V / AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM7-10(\*V60HZ)



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | DILM7-10(*V60HZ)              |
| Catalog number  | -                             |
| Category        | Power contactor, AC switching |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-5C83DF37EF                 |
| Generated       | 2026-08-06                    |

**Product Overview**

Contactor, 3p + 1N / O, 3kW / 400V / AC3

Power contactor; Screw connection; 3 poles + 1 NO; 7 A; 3 kW; 400 V; AC-3; \* V 60 Hz

Contactor, 3 pole, 380 V 400 V 3 kW, 1 N/O, \*V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I<sub>e</sub> = 7 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I<sub>th</sub> = I<sub>e</sub> = 22 A, enclosed: I<sub>th</sub> = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I<sub>th</sub> = 50 A, enclosed: I<sub>th</sub> = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 3.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1 kW, 380 V 400 V: P = 2.2 kW, 660 V 690 V: P = 2.9 kW, Can be combined with auxiliary contact: DILM32-XHI..., DILA-XHI(V)..., Contacts N/O = Normally open: 1 N/O, Instructions: Contacts....

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Contactors up to 170A

**Additional Product Information**

Contactor, 3 pole, 380 V 400 V 3 kW, 1 N/O, \*V 60 Hz, AC operation, Screw terminals  
Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors:

starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V:  $I_e = 7$  A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C:  $I_{th} = I_e = 22$  A, enclosed:  $I_{th} = 18$  A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open:  $I_{th} = 50$  A, enclosed:  $I_{th} = 45$  A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V:  $P = 2.2$  kW, 380 V 400 V:  $P = 3$  kW, 660 V 690 V:  $P = 3.5$  kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V:  $P = 1$  kW, 380 V 400 V:  $P = 2.2$  kW, 660 V 690 V:  $P = 2.9$  kW, Can be combined with auxiliary contact: DILM32-XHI., DILA-XHI(V)\_, Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operationDelivery program

Product rangeContactorsApplicationContactors for MotorsSubrangeContactors up to 170 A, 3 poleUtilization categoryAC-1: Non-inductive or slightly inductive loads, resista...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM7-10(\*V60HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.