

INDUSTRIAL COMPONENT DATA

DILEM-10(48V50HZ) 010020 Y7-10020 EATON ELECTRIC Contactor, 3p+1N/O, 4kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILEM-10(48V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILEM-10(48V50HZ)
Catalog number	Y7-10020
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-1E5FB92583
Generated	2026-08-06

Product Overview

Contactor, 3p+1N/O, 4kW/400V/AC3

Mini-Power Contactor Screw Connection 3 Pole + 1 NO 9 A 4

Eaton Moeller® series DILEM Contactor, 48 V 50 Hz, 3 pole, 380 V 400 V, 4 kW, Contacts N/O = Normally open= 1 N/O, Screw terminals, AC operation

Contactor, Application: Mini Contactors for Motors and Resistive Loads, DILEM contactors, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: With auxiliary contact, Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 9 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 22 A, enclosed: I_{th} = 16 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 50 A, enclosed: I_{th} = 40 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 4 kW, 660 V 690 V: P = 4 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1.5 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 3 kW, For use with: ...DILEM, ...DILE, Contacts N/O = Normally open:....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILEM Mini contactor Catalog Number 010020 Model Code DILEM-10(48V50HZ)

EAN 4015080100201 Product Length/Depth 52 mm Product Height 58 mm Product Width 45 mm Product Weight 0.17 kg

Certifications VDE 0660

CSA

UL 508

CSA File No.: 012528

UL

IEC/EN 60947-4-1

CSA-C22.2 No. 14-05

CSA Class No.: 3211-04

IEC/EN 60947

CE

UL File No.: E29096

UL Category Control No.: NLDX Catalog Notes Also tested according to AC-3e. Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with: Auxiliary contact Number Of Poles Three-pole General

Application Mini Contactors for Motors and Resistive Loads Lifespan, mechanical 10,000,000 Operations

150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A)

200,000 Operations (at 240 V, AC-15)

7,000,000 Operations (Coil 50/60 Hz) Mounting position As required (except vertical with terminals A1/A2 at the bottom)

Operating frequency 9000 mechanical Operations/h Overvoltage category III Pollution degree 3 Product category

Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

20 g, N/C auxiliary contact, Basic unit with auxiliary contact modul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILEM-10(48V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.