

INDUSTRIAL COMPONENT DATA

DILM9-10(24V50/60HZ) 276694 Y7-276694 EATON ELECTRIC Contactor, 3p+1N/O, 4kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM9-10(24V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM9-10(24V50/60HZ)
Catalog number	Y7-276694
Category	Power contactor, AC switching
Minimum order	1 unit
Document ID	EO-DA1E21EA1D
Generated	2026-08-06

Product Overview

Contactor, 3p+1N/O, 4kW/400V/AC3

DILM9-10(24V50/60HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 4 kW, 1 N/O, 24 V 50/60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 9 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole , 50 - 60 Hz Open at 40 °C: I_{th} =I_e= 22 A, enclosed: I_{th}= 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 50 A, enclosed: I_{th}= 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 2.5 kW, 380 V 400 V: P= 4 kW, 660 V 690 V: P= 4.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 1.5 kW, 380 V 400 V: P= 2.5 kW, 660 V 690 V: P= 3.6 kW, Can be combined with auxiliary contact: DILM32-XHI., DILA-XHI(V)., Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC opera...

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Rated control supply voltage AC 50 Hz (EF003978)	24 V
Rated control supply voltage AC 60 Hz (EF003979)	24 V
Rated control supply voltage DC (EF003980)	0 V
Voltage type for actuating (EF008242)	AC
Number of normally closed contacts as main contact (EF001375)	0

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of normally open contacts as main contact (EF001374)	3
Type of electrical connection of main circuit (EF006819)	Screw connection
Operating voltage AC 50 Hz (EF008206)	24 V
Operating voltage AC 60 Hz (EF008207)	24 V
Rated operation current I _e at AC-1, 400 V (EF001393)	22 A
Rated operation current I _e at AC-3, 400 V (EF001392)	9 A
Rated operation power at AC-3, 400 V (EF001364)	4 kW
Rated operation current I _e at AC-4, 400 V (EF008495)	6 A
Rated operation power at AC-4, 400 V (EF008496)	2.5 kW
Rated operation power NEMA (EF011960)	3.7 kW
Number of auxiliary contacts as normally open contact (EF001376)	1
Number of auxiliary contacts as normally closed contact (EF001377)	0
Modular version (EF001126)	No
Width (EF000008)	45 mm
Height (EF000040)	68 mm
Depth (EF000049)	75 mm

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor

Catalog Number 276694

Model Code DILM9-10(24V50/60HZ)

EAN 4015082766948

Product Length/Depth 75 mm

Product Height 68 mm

Product Width 45 mm

Product Weight 0.24 kg

Certifications CSA File No.: 012528

CE

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLDX

CSA

VDE 0660

CSA Class No.: 2411-03, 3211-04

UL

UL 60947-4-1

IEC/EN 60947-4-1

IEC/EN 60947

UL File No.: E29096

Features & Functions

Number of poles Three-pole

Number of poles Three-pole

Number of poles Three-pole

General information

Application Contactors for Motors

Connection Screw terminals

Lifespan, mechanical 7,000,000 Operations (Coil 50/60 Hz)

10,000,000 Operations (AC operated)

Operating frequency 9000 mechanical Operations/h (AC operated)

Overvoltage category III

Pollution degree 3

Product category Contactors

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp) 8000 V AC

Resistance per pole 2.5 mΩ

Suitable for Also motors with efficiency class IE3

Utili...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM9-10(24V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.