


INDUSTRIAL COMPONENT DATA

**DILM250-S/22(220-240V50/60HZ) 274190 Y7-274190 EATON
ELECTRIC Contactor, 3p+2N/O+2N/C, 132kW/400V/AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM250-S/22(220-240V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM250-S/22(220-240V50/60HZ)
Catalog number	Y7-274190
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-6060920CF3
Generated	2026-08-06

Product Overview

Contactor, 3p+2N/O+2N/C, 132kW/400V/AC3

DILM250-S/22(220-240V50/60HZ)

Eaton Moeller® series DILM Contactor, 380 V 400 V 132 kW, 2 N/O, 2 NC, 220 - 240 V 50/60 Hz, AC operation, Screw connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM Contactor Catalog Number 274190 Model Code

DILM250-S/22(220-240V50/60HZ) EAN 4015082741907 Product Length/Depth 208 mm Product Height 189 mm Product Width 140 mm Product Weight 6.71 kg Certifications IEC/EN 60947-4-1

UL File No.: E29096

UL Category Control No.: NLDX

VDE 0660

UL 60947-4-1

CSA Class No.: 3211-04

UL/CSA

CSA File No. 1017510

North America (UL listed, CSA certified)

EN 45545: Fire protection on railway vehicles

IEC 61373: Vibration and shock, tested for category 1 class B

CE marking Catalog Notes General

Accessories Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA Application
Contactors for Motors Connection Screw terminals Degree of protection IP00 Electromagnetic compatibility Designed for
operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring
additional noise suppression. Fitted with: Suppressor circuit in actuating electronics Lifespan, electrical 100,000 Operations
(at Condensor operation) Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 3000
mechanical Operations/h (AC operated)
200 Operations/h Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and
back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN
50274) Rated impulse withstand voltage (Uimp) 80...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM250-S/22(220-240V50/60HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.