

INDUSTRIAL COMPONENT DATA

DILM50-22(RDC24) 277876 Y7-277876 EATON ELECTRIC Contactor, 3p+2N/O+2N/C, 22kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM50-22(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM50-22(RDC24)
Catalog number	Y7-277876
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-C1115D71B2
Generated	2026-08-06

Product Overview

Contactor, 3p+2N/O+2N/C, 22kW/400V/AC3

DILM50-22(RDC24)

Eaton Moeller® series DILM Contactor, 380 V 400 V 22 kW, 2 N/O, 2 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals

Contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Rated operational current AC-3 380 V 400 V: I_e = 50 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 80 A, enclosed: I_{th} = 58 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 162 A, enclosed: I_{th} = 145 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 15.5 kW, 380 V 400 V: P = 22 kW, 660 V 690 V: P = 30 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 6 kW, 380 V 400 V: P = 10 kW, 660 V 690 V: P = 14 kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, with mirror conta...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 277876 Model Code DILM50-22(RDC24) EAN 4015082778767 Product Length/Depth 147 mm Product Height 115 mm Product Width 55 mm Product Weight 1.082 kg

Certifications UL 60947-4-1

IEC/EN 60947-4-1

UL

UL Category Control No.: NLDX

CSA

CE

IEC/EN 60947

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Suppressor circuit in actuating electronics

Mirror contact General

Application Contactors for Motors Lifespan, mechanical 7,000,000 Operations (Coil 50/60 Hz)

10,000,000 Operations (DC operated) Operating frequency 5000 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 1.9 m Ω Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type DC Ambient conditions, mechanical Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O aux...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM50-22(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.