

INDUSTRIAL COMPONENT DATA

DILH2600/22(RAW250) 125945 Y7-125945 EATON ELECTRIC Contactor, 3p+2N/O+2N/C, 2600A/AC1

Brand: EATON - MOELLER | Manufacturer Part Number: DILH2600/22(RAW250)



Manufacturer	EATON - MOELLER
MPN / Reference	DILH2600/22(RAW250)
Catalog number	Y7-125945
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-9D874316F8
Generated	2026-08-05

Product Overview

Contactor, 3p+2N/O+2N/C, 2600A/AC1

DILH2600/22(RAW250)

Contactor, I_{th} = I_e: 3185 A, RAW 250: 230 - 250 V 50 - 60 Hz/230 - 350 V DC, AC and DC operation, Screw connection
Contactor, Application: Mains contactors for resistive loads from 1000 A, AC -1 contactors greater than 1000 A, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, Connection technique: Screw connection, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 3185 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 6500 A, For use with: DILM820-XHI..., Instructions: integrated suppressor circuit in actuating electronics, 660 V, 690 V or 1000 V: not directly reversing, Voltage AC/DC: AC and DC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

Contactor, I_{th} = I_e: 3185 A, RAW 250: 230 - 250 V 50 - 60 Hz/230 - 350 V DC, AC and DC operation, Screw connection
Contactor, Application: Mains contactors for resistive loads from 1000 A, AC -1 contactors greater than 1000 A, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, Connection technique: Screw connection, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 3185 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 6500 A, For use with: DILM820-XHI..., Instructions: integrated suppressor circuit in actuating electronics, 660 V, 690 V or 1000 V: not directly reversing, Voltage AC/DC: AC and DC operation
Delivery program

Product range: Contactors
Application: Mains contactors for resistive loads from 1000 A
Subrange: AC -1 contactors greater than 1000 A
Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces
Connection technique: Screw connection
Rated operational current: AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open at 40 °C [$I_{th}=I_e$] 3185 A
AC-1 Conventional free air thermal current, 1 pole open [I_{th}] 6500 A
Contact sequence: For use with DILM820-XHI...
Actuating voltage: RAW 250: 230 - 250 V 50 - 60 Hz / 230 - 350 V DC
Voltage AC/DC: AC and DC operation
Auxiliary contacts: possible variants at auxiliary contact module fitting options on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SAS
Side mounting auxiliary contact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILH2600/22(RAW250) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.