

INDUSTRIAL COMPONENT DATA

**DILMP20(380V50/60HZ) 276979 XTCF020B00AR EATON
ELECTRIC 276979 DILMP20(380V50/60HZ)**

Brand: EATON - MOELLER | Manufacturer Part Number: DILMP20(380V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMP20(380V50/60HZ)
Catalog number	XTCF020B00AR
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-85931917AD
Generated	2026-08-06

Product Overview

276979 DILMP20(380V50/60HZ)

Power Contactor Screw Connection 4 Pole 20 A AC-1 380 V

Contactor, 4 pole, 22 A, 380 V 50/60 Hz, AC operation

Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: I_e= 12 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 22 A, enclosed: I_{th}= 18 A, Conventional free air thermal current, 1 pole open: I_{th}= 60 A, enclosed: I_{th}= 54 A, 220 V 230 V: P= 3.5 kW, 380 V 400 V: P= 5.5 kW, 660 V 690 V: P= 6.5 kW, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 4 pole, 22 A, 380 V 50/60 Hz, AC operation Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: I_e= 12 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 22 A, enclosed: I_{th}= 18 A, Conventional free air thermal current, 1 pole open: I_{th}= 60 A, enclosed: I_{th}= 54 A, 220 V 230 V: P= 3.5 kW, 380 V 400 V: P= 5.5 kW, 660 V 690 V: P= 6.5 kW, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation Delivery program

Product range
Contactors Application
Contactors for 4 pole electric consumers
Subrange
Contactors up to 200 A, 4 pole
Utilization category
AC-1: Non-inductive or slightly inductive loads, resistance furnaces
AC-3/AC-3e: Normal AC induction motors: Starting, switching off while running
Connection technique
Screw terminals
Number of poles
4 pole
Rated operational current
AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz at 40 °C [$I_{th}=I_e$]
22 AAC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz at 50 °C [$I_{th}=I_e$]
21 AAC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz at 55 °C [$I_{th}=I_e$]
20.5 AAC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz at 60 °C [$I_{th}=I_e$]
20 A
Contact sequence
For use with
DILM32-XHI(C)...
DILA-XHI(V)(C)...
Act...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMP20(380V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.