

INDUSTRIAL COMPONENT DATA

DILMP45-10(*V60HZ) 109817 EATON ELECTRIC Contactor, 4p+1N/O, 45A/AC1

Brand: EATON - MOELLER | Manufacturer Part Number: DILMP45-10(*V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMP45-10(*V60HZ)
Catalog number	109817
Category	Power contactor, AC switching
Minimum order	10 Pcs
Document ID	EO-E6CD84CAB4
Generated	2026-08-04

Product Overview

Contactor, 4p+1N/O, 45A/AC1

Power contactor; Screw connection; 4 poles + 1 NO; 45 A; AC-1; * V 60 Hz

Contactor, 4 pole, 45 A, 1 N/O, *V 60 Hz, AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 4 pole, 45 A, 1 N/O, *V 60 Hz, AC operation

Contactor, Application: Contactors for 4 pole electric consumers, Contactors up to 200 A, 4 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, Connection technique: Screw terminals, Number of poles: 4 pole, 380 V 400 V: I_e= 25 A, Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 45 A, enclosed: I_{th}= 36 A, Conventional free air thermal current, 1 pole open: I_{th}= 117 A, enclosed: I_{th}= 105 A, 220 V 230 V: P= 7.5 kW, 380 V 400 V: P= 11 kW, 660 V 690 V: P= 14 kW, Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation Delivery program

Product range Contactors Application Contactors for 4 pole electric consumers Subrange Contactors up to 200 A, 4 pole Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

NAC-3: Normal AC induction motors: starting, switch off during running Connection technique Screw terminals Number of poles 4 pole Rated operational current AC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 40 °C [I_{th}=I_e] 45 A AC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 50 °C [I_{th}=I_e] 41 A AC-1Conventional free air thermal current, 3 pole, 50 - 60 Hzat 60 °C

[lth=le] 39 A Contacts....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMP45-10(*V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.