

## INDUSTRIAL COMPONENT DATA

# CMUC230/25-22 137403 Y7-137403 EATON ELECTRIC

## Installation contactor, 230 VAC/DC, 2N/C+2N/O, 25A

Brand: EATON - MOELLER | Manufacturer Part Number: CMUC230/25-22



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | EATON - MOELLER                               |
| MPN / Reference | CMUC230/25-22                                 |
| Catalog number  | Y7-137403                                     |
| Category        | Installation contactor for distribution board |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-25221A3438                                 |
| Generated       | 2026-08-04                                    |

### Product Overview

Installation contactor, 230 VAC/DC, 2N/C+2N/O, 25A

CMUC230/25-22

Eaton Distribution parts. Installation contactor, 230 VAC/DC, 2N/C+2N/O, 25A

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Modular Switchgear - Others and Accessories

### Additional Product Information

## General specifications

Product Name Eaton Distribution parts Catalog Number 137403 Model Code CMUC230/25-22 EAN 4015081341856

Product Length/Depth 85 mm Product Height 60 mm Product Width 35 mm Product Weight 0.22 kg Compliances RoHS conform Product specifications

Amperage Rating 25 A Features Additional equipment possible

Hum-free Degree of protection IP20 Equipment heat dissipation, current-dependent 7.5 W Ambient operating temperature - max 60 °C Ambient operating temperature - min -40 °C Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Incandescent lamp load - max 3000 W Load fluorescent lamp - max 1360 VA Load fluorescent lamp (duo circuit) - max 2552 VA Load fluorescent lamp (parallel compensated) - max 1360 VA Number of contacts (normally closed contacts) 2 Number of contacts (normally open contacts) 2 Number of modular spacings 2 Rated operating voltage (Ue) - max 440 V Rated operating voltage (Ue) - min 440 V Rated operational current for specified heat dissipation (In) 25 A Static heat dissipation, non-current-dependent 0 W Utility category 0 Voltage rating (excitation) - max 253 V Voltage rating (excitation) - min 195.5 V Built-in depth 69.5 mm Voltage type AC/DC Utilization category (according to EN IEC 60947-4-1)

AC-1

ETIM for 137403 Modular devices for distribution board/surface mounting (EC001653)

Feature Name

Feature Value

Rated operating voltage (EF001435)

440 V

Rated operation current (EF007679)

25 A

Utilization category accord...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CMUC230/25-22 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.