

INDUSTRIAL COMPONENT DATA

CMUC230/25-40 137309 Y7-137309 EATON ELECTRIC

Installation contactor, 230 VAC/DC, 4N/O, 25A

Brand: EATON - MOELLER | Manufacturer Part Number: CMUC230/25-40



Manufacturer	EATON - MOELLER
MPN / Reference	CMUC230/25-40
Catalog number	Y7-137309
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-5F3018C792
Generated	2026-08-04

Product Overview

Installation contactor, 230 VAC/DC, 4N/O, 25A

CMUC230/25-40

Eaton Distribution parts. Installation contactor, 230 VAC/DC, 4N/O, 25A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 137309 Model Code CMUC230/25-40 EAN 4015081341818

Product Length/Depth 85 mm Product Height 60 mm Product Width 35 mm Product Weight 0.22 kg Compliances RoHS conform Product specifications

Amperage Rating 25 A Features Additional equipment possible

Hum-free Degree of protection IP20 Equipment heat dissipation, current-dependent 11.5 W Ambient operating temperature - max 60 °C Ambient operating temperature - min -40 °C Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Incandescent lamp load - max 3000 W Load fluorescent lamp - max 1360 VA Load fluorescent lamp (duo circuit) - max 2552 VA Load fluorescent lamp (parallel compensated) - max 1360 VA Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 4 Number of modular spacings 2 Rated operating voltage (Ue) - max 440 V Rated operating voltage (Ue) - min 440 V Rated operational current for specified heat dissipation (In) 25 A Static heat dissipation, non-current-dependent 0 W Utility category 0 Voltage rating (excitation) - max 253 V Voltage rating (excitation) - min 195.5 V Built-in depth 69.5 mm Voltage type AC/DC Utilization category (according to EN IEC 60947-4-1)

AC-1

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CMUC230/25-40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.